




## Flamco

Accessories for potable installations



PRESCOR B



SUPAMIX





## Flamco For the effective protection of your installation

The Prescor B boiler valves protect closed potable water systems against pressure surges. Because the water expands and because there is a non-return valve fitted, such a safeguard is a statutory requirement. Local standards, guidelines and water pressure must be respected when using Prescor B valves. Supamix FS and NHS are WRC listed valves with brass or chrome body.



The button shows product data.



PRESCOR B

When the pressure reaches the preset level, the Prescor B boiler valve will begin to drip so the pressure cannot rise any further.

If conditions lead to the pressure rising too quickly (above the preset level), the Prescor B boiler valve will open, creating a significant blow-off capacity. That is your lasting guarantee of safety against excess pressure.

### SUPAMIX ADVANTAGES

- ◆ Supamix FS are WRC listed valves to BS 1415 with ant-scale device for general use with fail safe protection.
- ◆ Supamix NHS are WRC approved valves in compliance with the National Health Service Model Engineering Specification D08 for Healthcare premises.
- ◆ Supamix NHS approved for high/low pressure for showers and wash basins, low pressure for bidets.



SUPAMIX


- ◆ Prescor B safety valves with solid brass housing.
- ◆ All Prescor B valves are factory tested and CE-certified. They can be used in combination with any water heating system and are allowed for temperatures up to 140 °C.
- ◆ Because of the “pop” effect Prescor B valves have a high blow-off capacity.
- ◆ Supamix FS: brass body complete with non-return valves and strainers.
- ◆ Supamix NHS: Chrome body complete with non-return valves and strainers.



### Models and dimensions of Prescor B safety valves

Type	Boiler capacity in kW	Connection dimensions screw thread (Internal)		Dimensions in mm				For hotwater appliances	Code number
		A	B	C	D	E	F		
<b>6 bar</b>									
Prescor B 1/2"	75	1/2"	1/2"	65	49	22	30	to 200 litres	27100
Prescor B 3/4"	150	3/4"	1"	94	61	33	42.5	to 1000 litres	27110
Prescor B 1"	250	1"	1 1/4"	98.5	75.5	38	53	to 5000 litres	29005
Prescor SB 1 1/4"	350	1 1/4"	1 1/2"	214	106	48	58	-	29008
Prescor SB 1 1/2"	600	1 1/2"	2"	226	116	53	68	-	29011
Prescor SB 2	900	2"	2 1/2"	242	130	62	82	-	29015
<b>8 bar</b>									
Prescor B 1/2"	75	1/2"	1/2"	65	49	22	30	to 200 litres	27101
Prescor B 3/4"	150	3/4"	1"	94	61	33	42.5	to 1000 litres	27111
Prescor B 1"	250	1"	1 1/4"	98.5	75.5	38	53	to 5000 litres	29006
Prescor SB 1 1/4"	350	1 1/4"	1 1/2"	214	106	48	58	-	29009
Prescor SB 1 1/2"	600	1 1/2"	2"	226	116	53	68	-	29012
Prescor SB 2	900	2"	2 1/2"	242	130	62	82	-	29016
<b>10 bar</b>									
Prescor B 1/2"	75	1/2"	1/2"	65	49	22	30	to 200 litres	27102
Prescor B 3/4"	150	3/4"	1"	94	61	33	42.5	to 1000 litres	27112
Prescor B 1"	250	1"	1 1/4"	98.5	75.5	38	53	to 5000 litres	29007
Prescor SB 1 1/4"	350	1 1/4"	1 1/2"	214	106	48	58	-	29010
Prescor SB 1 1/2"	600	1 1/2"	2"	226	116	53	68	-	29013
Prescor SB 2	900	2"	2 1/2"	242	130	62	82	-	29017


PRESCOR B



### Versions and dimensions Supamix FS

Type	System connection mm	A	Dimensions in mm B	C	Code number
Supamix FS 15	15	140	130	60	FR SUPA FS 15
Supamix FS 22	22	140	130	60	FR SUPA FS 22

SUPAMIX



### Versions and dimensions Supamix NHS

Type	System connection mm	A	Dimensions in mm B	C	Code number
Supamix NHS 15	15	140	130	60	FR SUPA N 15
Supamix NHS 22	22	140	130	60	FR SUPA N 22



PRESCOR B



SUPAMIX

## ACCESSORIES FOR POTABLE INSTALLATIONS

◆ CONTENTS	PAGE
◆ Advantages of Prescor and Supamix valves	5.2
◆ Tables and technical data	5.3

On the CD which accompanies this brochure, you will find plenty more information.

Copyright Flamco UK Ltd.

No part of this publication may be reproduced in any way without explicit reference to the source. The data listed applies solely to Flamco products. Flamco UK is in no way liable for the misuse of the equipment or incorrect interpretation of the technical information contained herein. We reserve the right to make technical alterations.

Flamco UK Limited conditions of sale apply.



# Flamco

**Flamco UK Ltd.**

Unit 4, St Michael's Road

Lea Green Industrial Estate

St Helens, Merseyside WA9 4WZ

United Kingdom

Tel: +44(0)1744 818100

Fax: +44(0)1744 830400

info@flamco.co.uk

www.flamco.co.uk